

Card Master PCI-FD1

Features

- Comply with PCI power management
- Comply with ACPI
- 1 front /1rear slot, access from rear of PC
- Accept Type I/II/III Cards
- Comply with PCI Local Bus Specification Rev.2.1
- Comply with 1995 PC Card (CardBus) Standard
- ExCa compatible Registers are mapped in Memory
- Use T/I PCI 1225 PCMCIA controller
- Support two PC Card or CardBus Slots with Hot Insertion and Removal
- Mix and Match 5V/3.3V PC Card 16 bits Cards
- Support Burst Transfers to Maximize Data Throughput on both PCI Buses
- Supports Distributed DMA and PC/PCI DMA
- Support 16 bit DMA on both PC Card Sockets or I/O space

Specification

- LED indicators: Power, Busy and Battery Low
- Power Supply Voltage : 5V and 3.3V Typical
- Operation Temperature : 0°C—70°C
- Storage Temperature : -20°C—85°C
- Relative Humidity : Max 90%
- Dimensions 162mm(L) x 107.8mm(W) x 15mm(H)
For I/F Card Standard 3.5" FDD For Factor

Package Contents

The PCI-FD1 front +rear –mounted PCI-bus PCMCIA drive includes the following items:

- One PCI-bus expansion card with PCMCIA connector (model no.PAC-SDD-04A-V5.1)
- One front-mounted 3.5" FDD from-factor PCMCIA drive (model no. PAC-SDD-04A-V.5.1 + PAC-SDD-04B-V.2.0)
- 50 Pin flat cable to connect front-mounted drive to PCI expansion card
- One utility diskettes containing devise driver. – P-Series for Win 98/2000/Me/NT
- This user's manual

