

Card Master PCI-IF2

Features

- Comply with PCI power management
- Comply with ACPI
- 2 rear slot, access from rear of PC
- Accept Type I/II/III Cards
- Comply with PCI Local Bus Specification Rev.2.1
- Comply with 1995 PC Card (CardBus) Standard
- ExCa compatible Registers are mapped in Memory
- Use T/I 1420 PCMCIA controller
- Support one PC Card or CardBus Slots with Hot Insertion and Removal
- Mix and Match 5V/3.3V PC Card 16/32 bits Cards
- Support Burst Transfers to Maximize Data Throughput on both PCI Buses
- Supports Distributed DMA and PC/PCI DMA
- Support 16/32 bit DMA on both PC Card Sockets or I/O space.

Specification

- Power Supply Voltage : 5V and 3.3V Typical
- Operation Temperature : 0°C—70°C
- Storage Temperature : -20°C—85°C
- Relative Humidity : Max 90%
- Dimensions 162mm(L) x 107.8mm(W) x 15mm(H)

Package Contents

The PCI-IF2 — 2 rear-mounted PCI-bus PCMCIA driver includes the following items:

- One PCI-bus expansion card with PCMCIA connector
(model no. PAC-SDD-011A-V.1.0)
- One utility diskettes containing devise driver. —P-Series for Win 98/2000/Me/NT
- This user's manual

